

FINAL



Loewen Inc
SUITE 400
2180 SATELITE BLVD.
DULUTH, GEORGIA 30097
www.loewen.com

Phone : 800-563-9367
Fax : 800-563-9361
Inside Rep : BRAD THIESSEN
Sales Rep : US HOUSE SALES

Order : 1572710
Suffix :
Invoice :
Div : 74

Order Acknowledgment

Customer Billing Information

Account : 890300	Order Date : 2021/01/25
The Sullivans	Revised Date : 2021/03/02
620 Admiralty Parade	Load Date : *Pending*
Port Royal, FL	Purchase Order : SULLIVAN 01-LOEWEN1
34102	Service Order :
UNITED STATES	Invoice Date :
Contact : Brad Thiessen	
Phone :	
Fax :	

TAG Name :

Customer Shipping Information

Account : 890300	Carrier : SOUTH EAST STATES
Engler Company, Inc.	Ship Via : LOEWEN TRUCK SYSTEM
340 9th St. N. #206	Instructions : LOEWEN TRUCK SYSTEM
Naples, FL	Ship Type : Direct
34102	
UNITED STATES	
Contact : Brad Thiessen	
Phone :	
Fax :	

Order : 1572710

Order Notes

ATTN:MIKE_PO#SULLIVAN_01_TAG-BCB-SULLIVAN
** SERVICE ORDER **

*

Line : 29.00	Model : 28AC	28 AWNING AND CASEMENT			(D)
Location: <u>Bedroom 2</u>		Cubic Feet: 9.000			
Qty : 1.00	U/M : EA	List :	2017.00	Disc% : 23.25	Net : 1,548.05 Total : 1,548.05

BUILD TYPE	: Complete Unit	SASH TYPE	: Triple Sash
UNIT STYLE	: Casement Style	GLAZING STOP	: Interior Profiled Glazing Stops
UNIT TYPE	: Traditional Operation	GRILLE TYPE	: SDL Grille
OPERATION	: Fixed	GRILLE COLOR	: White Clad (Std)
ENHANCED DP	: Enhanced Performance	GRILLE STYLE	: Colonial Grille
JAMB MOLDING	: Standard Moldings	GRILLE PATTERN	: 2W3H Pattern
FRAME WIDTH	: 760 MM	VERTICAL SIZE	: 3/4" (19mm)
FRAME HEIGHT	: 1500 MM	HORIZONTAL SIZE	: 3/4" (19mm)
UNIT SHAPE	: Rectangular (Or Square)	EXT PROFILE	: Ogee Exterior Profile
SPECIES	: Douglas Fir	INT PROFILE	: Ogee Interior Profile
FRAME FINISH	: White Clad (Std)	GRILLE SPACER	: 1 Airspace With Shadow Bars
SASH FINISH	: Sash Color Matches Frame Color	GRL SHADOW BAR	: Deep Shadow Bar
INT FRAME FIN	: Primed	GRILLE STD PATT	: Grille is a Standard Pattern
INT SASH FIN	: Primed	HARDWARE COLOR	: No Hardware Color
INT GRILLE FIN	: Primed	LOCK	: No Locks
JAMB	: 116 MM	SCREEN TYPE	: No Screen
BRICKMOLD	: No Exterior Casings Required	FLANGE	: All Four Sides
BRICKMOLD FIN	: No Casing Color	DRIPCAP	: Snap On Dripcap
SUBSILL	: No Casing Subsill/Sillnose	PKG	: Standard Packaging
GLAZING	: Stormforce Series IP D-Missile	DRAWING#	: 26075-07-00A
GLZ CONFIG	: CLR_3_366/B20-130/CLR_10.1SGP_NOC	APPROVAL#	: 26075-07-00A
GLASS TINT	: Clear Glass	QUALITY INSPECT	: QC must Inspect Prior to PKG
GLASS THICKNESS	: 3 MM Glass Thickness	WATER TEST	: Water Tested in the Field
LAMI GLASS	: 10.1MM SGP 3.9/.090/3.9	FRMNOSE	: Standard
COATING	: LOW E 366	MIDCMT	: QM_ITEM : G
SPACER FINISH	: BRZ Aluminum(20)Spacer Bar 13MM	MIDCMT	: AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
CERTIFIED	: Impact Certified		

Line : 30.00	Model : 28AC	28 AWNING AND CASEMENT			(D)
Location: <u>Bath 2</u>		Cubic Feet: 6.000			
Qty : 1.00	U/M : EA	List :	1353.00	Disc% : 23.25	Net : 1,038.43 Total : 1,038.43

BUILD TYPE	: Complete Unit	SASH TYPE	: Triple Sash
UNIT STYLE	: Casement Style	GLAZING STOP	: Interior Profiled Glazing Stops
UNIT TYPE	: Traditional Operation	GRILLE TYPE	: SDL Grille
OPERATION	: Fixed	GRILLE COLOR	: White Clad (Std)
ENHANCED DP	: Enhanced Performance	GRILLE STYLE	: Colonial Grille
JAMB MOLDING	: Standard Moldings	GRILLE PATTERN	: 2W2H Pattern
FRAME WIDTH	: 600 MM	VERTICAL SIZE	: 3/4" (19mm)
FRAME HEIGHT	: 1200 MM	HORIZONTAL SIZE	: 3/4" (19mm)
UNIT SHAPE	: Rectangular (Or Square)	EXT PROFILE	: Ogee Exterior Profile
SPECIES	: Douglas Fir	INT PROFILE	: Ogee Interior Profile
FRAME FINISH	: White Clad (Std)	GRILLE SPACER	: 1 Airspace With Shadow Bars
SASH FINISH	: Sash Color Matches Frame Color	GRL SHADOW BAR	: Deep Shadow Bar
INT FRAME FIN	: Primed	GRILLE STD PATT	: Grille is a Standard Pattern
INT SASH FIN	: Primed	HARDWARE COLOR	: No Hardware Color
INT GRILLE FIN	: Primed	LOCK	: No Locks
JAMB	: 116 MM	SCREEN TYPE	: No Screen
BRICKMOLD	: No Exterior Casings Required	FLANGE	: All Four Sides
BRICKMOLD FIN	: No Casing Color	DRIPCAP	: Snap On Dripcap
SUBSILL	: No Casing Subsill/Sillnose	PKG	: Standard Packaging
GLAZING	: Stormforce Series IP D-Missile	DRAWING#	: 26075-07-00A
GLZ CONFIG	: CLR_3_366/B20-130/CLR_10.1SGP_NOC	APPROVAL#	: 26075-07-00A
GLASS TINT	: Clear Glass	QUALITY INSPECT	: QC must Inspect Prior to PKG
GLASS THICKNESS	: 3 MM Glass Thickness	WATER TEST	: Water Tested in the Field
LAMI GLASS	: 10.1MM SGP 3.9/.090/3.9	FRMNOSE	: Standard
COATING	: LOW E 366	MIDCMT	: QM_ITEM : H
SPACER FINISH	: BRZ Aluminum(20)Spacer Bar 13MM	MIDCMT	: AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
CERTIFIED	: Impact Certified		

Line : 39.00

Model : 28AC

28 AWNING AND CASEMENT

(D)

Location: Kitchen

Cubic Feet: 6.000

Qty : 1.00

U/M : EA

List :

1423.00

Disc% : 23.25

Net :

1,092.15

Total : 1,092.15

BUILD TYPE : Complete Unit
 UNIT STYLE : Casement Style
 UNIT TYPE : Traditional Operation
 OPERATION : Fixed
 ENHANCED DP : Enhanced Performance
 JAMB MOLDING : Standard Moldings
 FRAME WIDTH : 600 MM 23 5/8"
 FRAME HEIGHT : 1200 MM 47 1/4"
 UNIT SHAPE : Rectangular (Or Square)
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 BRICKMOLD : No Exterior Casings Required
 BRICKMOLD FIN : No Casing Color
 SUBSILL : No Casing Subsill/Sillnose
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
 COATING : LOW E 366
 SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
 CERTIFIED : Impact Certified

SASH TYPE : Triple Sash
 GLAZING STOP : Interior Profiled Glazing Stops
 GRILLE TYPE : SDL Grille
 GRILLE COLOR : White Clad (Std)
 GRILLE STYLE : Colonial Grille
 GRILLE PATTERN : 2W3H Pattern
 VERTICAL SIZE : 3/4" (19mm)
 HORIZONTAL SIZE : 3/4" (19mm)
 EXT PROFILE : Ogee Exterior Profile
 INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Grille is a Standard Pattern
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 FLANGE : All Four Sides
 DRIPCAP : Snap On Dripcap
 PKG : Standard Packaging
 DRAWING# : 26075-07-00A
 APPROVAL# : 26075-07-00A
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested In the Field
 FRMNOSE : Standard
 MIDCMT : QM_ITEM : U
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

Line : 49.00

Model : 28AC

28 AWNING AND CASEMENT

(D)

Location: Bedroom 5

Cubic Feet: 10.000

Qty : 1.00

U/M : EA

List :

2102.00

Disc% : 23.25

Net :

1,613.29

Total : 1,613.29

BUILD TYPE : Complete Unit
 UNIT STYLE : Casement Style
 UNIT TYPE : Traditional Operation
 OPERATION : Fixed
 ENHANCED DP : Enhanced Performance
 JAMB MOLDING : Standard Moldings
 FRAME WIDTH : 800 MM 31 1/2"
 FRAME HEIGHT : 1500 MM 69 1/16"
 UNIT SHAPE : Rectangular (Or Square)
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 BRICKMOLD : No Exterior Casings Required
 BRICKMOLD FIN : No Casing Color
 SUBSILL : No Casing Subsill/Sillnose
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
 COATING : LOW E 366
 SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
 CERTIFIED : Impact Certified

SASH TYPE : Triple Sash
 GLAZING STOP : Interior Profiled Glazing Stops
 GRILLE TYPE : SDL Grille
 GRILLE COLOR : White Clad (Std)
 GRILLE STYLE : Colonial Grille
 GRILLE PATTERN : 2W3H Pattern
 VERTICAL SIZE : 3/4" (19mm)
 HORIZONTAL SIZE : 3/4" (19mm)
 EXT PROFILE : Ogee Exterior Profile
 INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Grille is a Standard Pattern
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 FLANGE : All Four Sides
 DRIPCAP : Snap On Dripcap
 PKG : Standard Packaging
 DRAWING# : 26075-07-00A
 APPROVAL# : 26075-07-00A
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested In the Field
 FRMNOSE : Standard
 MIDCMT : QM_ITEM : BB
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

*

Line : 50.00 Model : 28AC 28 AWNING AND CASEMENT (D)
 Location: Bath 4 Cubic Feet: 3.000
 Qty : 1.00 U/M : EA List : 920.00 Disc% : 23.25 Net : 706.10 Total : 706.10

BUILD TYPE : Complete Unit
 UNIT STYLE : Casement Style
 UNIT TYPE : Traditional Operation
 OPERATION : Fixed
 ENHANCED DP : Enhanced Performance
 JAMB MOLDING : Standard Moldings
 FRAME WIDTH : 400 MM 15 3/4"
 FRAME HEIGHT : 800 MM 31 1/2"
 UNIT SHAPE : Rectangular (Or Square)
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 BRICKMOLD : No Exterior Casings Required
 BRICKMOLD FIN : No Casing Color
 SUBSILL : No Casing Subsill/Sillnose
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
 COATING : LOW E 366
 SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
 CERTIFIED : Impact Certified

SASH TYPE : Triple Sash
 GLAZING STOP : Interior Profiled Glazing Stops
 GRILLE TYPE : SDL Grille
 GRILLE COLOR : White Clad (Std)
 GRILLE STYLE : Colonial Grille
 GRILLE PATTERN : 2W2H Pattern
 VERTICAL SIZE : 3/4" (19mm)
 HORIZONTAL SIZE : 3/4" (19mm)
 EXT PROFILE : Ogee Exterior Profile
 INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Grille is a Standard Pattern
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 FLANGE : All Four Sides
 DRIPCAP : Snap On Dripcap
 PKG : Standard Packaging
 DRAWING# : 26075-07-00A
 APPROVAL# : 26075-07-00A
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : QM_ITEM : CC
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

Line : 53.00 Model : 28AC 28 AWNING AND CASEMENT (D)
 Location: Bedroom 4 Cubic Feet: 10.000
 Qty : 1.00 U/M : EA List : 2102.00 Disc% : 23.25 Net : 1,613.29 Total : 1,613.29

BUILD TYPE : Complete Unit
 UNIT STYLE : Casement Style
 UNIT TYPE : Traditional Operation
 OPERATION : Fixed
 ENHANCED DP : Enhanced Performance
 JAMB MOLDING : Standard Moldings
 FRAME WIDTH : 800 MM 31 1/2"
 FRAME HEIGHT : 1500 MM 59 1/16"
 UNIT SHAPE : Rectangular (Or Square)
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 BRICKMOLD : No Exterior Casings Required
 BRICKMOLD FIN : No Casing Color
 SUBSILL : No Casing Subsill/Sillnose
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
 COATING : LOW E 366
 SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
 CERTIFIED : Impact Certified

SASH TYPE : Triple Sash
 GLAZING STOP : Interior Profiled Glazing Stops
 GRILLE TYPE : SDL Grille
 GRILLE COLOR : White Clad (Std)
 GRILLE STYLE : Colonial Grille
 GRILLE PATTERN : 2W3H Pattern
 VERTICAL SIZE : 3/4" (19mm)
 HORIZONTAL SIZE : 3/4" (19mm)
 EXT PROFILE : Ogee Exterior Profile
 INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Grille is a Standard Pattern
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 FLANGE : All Four Sides
 DRIPCAP : Snap On Dripcap
 PKG : Standard Packaging
 DRAWING# : 26075-07-00A
 APPROVAL# : 26075-07-00A
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : QM_ITEM : FF
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

*

Line : 59.00	Model : 28AC	28 AWNING AND CASEMENT			(D)
Location: _Open to Study		Cubic Feet: 28.000			
Qty : 7.00	U/M : EA	List : 885.00	Disc% : 23.25	Net : 679.24	Total : 4,754.68

BUILD TYPE : Complete Unit
UNIT STYLE : Casement Style
UNIT TYPE : Traditional Operation
OPERATION : Fixed
ENHANCED DP : Enhanced Performance
JAMB MOLDING : Standard Moldings
FRAME WIDTH : 600 MM 19 11/16"
FRAME HEIGHT : 900 MM 35 7/16"
UNIT SHAPE : Rectangular (Or Square)
SPECIES : Douglas Fir
FRAME FINISH : White Clad (Std)
SASH FINISH : Sash Color Matches Frame Color
INT FRAME FIN : Primed
INT SASH FIN : Primed
JAMB : 116 MM 4 9/16"
BRICKMOLD : No Exterior Casings Required
BRICKMOLD FIN : No Casing Color
SUBSILL : No Casing Subsill/Sillnose
GLAZING : Stormforce Series IP D-Missile
GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
GLASS TINT : Clear Glass

GLASS THICKNESS : 3 MM Glass Thickness
LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
COATING : LOW E 366
SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
CERTIFIED : Impact Certified
SASH TYPE : Triple Sash
GLAZING STOP : Interior Profiled Glazing Stops
HARDWARE COLOR : No Hardware Color
LOCK : No Locks
SCREEN TYPE : No Screen
FLANGE : All Four Sides
DRIPCAP : Snap On Dripcap
PKG : Standard Packaging
DRAWING# : 26075-07-00A
APPROVAL# : 26075-07-00A
QUALITY INSPECT : QC must Inspect Prior to PKG
WATER TEST : Water Tested in the Field
FRMNOSE : Standard
MIDCMT : QM_ITEM : HH-NN
MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

Line : 60.00	Model : 28AC	28 AWNING AND CASEMENT			(D)
Location: _Open to Study		Cubic Feet: 16.000			
Qty : 4.00	U/M : EA	List : 887.00	Disc% : 23.25	Net : 680.77	Total : 2,723.08

BUILD TYPE : Complete Unit
UNIT STYLE : Casement Style
UNIT TYPE : Traditional Operation
OPERATION : Fixed
ENHANCED DP : Enhanced Performance
JAMB MOLDING : Standard Moldings
FRAME WIDTH : 600 MM 19 11/16"
FRAME HEIGHT : 900 MM 35 7/16"
UNIT SHAPE : Rectangular (Or Square)
SPECIES : Douglas Fir
FRAME FINISH : White Clad (Std)
SASH FINISH : Sash Color Matches Frame Color
INT FRAME FIN : Primed
INT SASH FIN : Primed
JAMB : 116 MM 4 9/16"
BRICKMOLD : No Exterior Casings Required
BRICKMOLD FIN : No Casing Color
SUBSILL : No Casing Subsill/Sillnose
GLAZING : Stormforce Series IP D-Missile
GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
GLASS TINT : Clear Glass

GLASS THICKNESS : 3 MM Glass Thickness
LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
COATING : LOW E 366
SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
CERTIFIED : Impact Certified
SASH TYPE : Triple Sash
GLAZING STOP : Interior Profiled Glazing Stops
HARDWARE COLOR : No Hardware Color
LOCK : No Locks
SCREEN TYPE : No Screen
FLANGE : All Four Sides
DRIPCAP : Snap On Dripcap
PKG : Standard Packaging
DRAWING# : 26075-07-00A
APPROVAL# : 26075-07-00A
QUALITY INSPECT : QC must Inspect Prior to PKG
WATER TEST : Water Tested in the Field
FRMNOSE : Standard
MIDCMT : QM_ITEM : PP-TT
MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

*

Line : 69.00	Model : 28AC	28 AWNING AND CASEMENT	(D)
Location: Bath 3		Cubic Feet: 6.000	
Qty : 1.00	U/M : EA	List : 1421.00	Disc% : 23.25
		Net : 1,090.62	Total : 1,090.62

BUILD TYPE : Complete Unit
 UNIT STYLE : Casement Style
 UNIT TYPE : Traditional Operation
 OPERATION : Fixed
 ENHANCED DP : Enhanced Performance
 JAMB MOLDING : Standard Moldings
 FRAME WIDTH : 500 MM 19 11/16"
 FRAME HEIGHT : 1400 MM 65 1/8"
 UNIT SHAPE : Rectangular (Or Square)
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 BRICKMOLD : No Exterior Casings Required
 BRICKMOLD FIN : No Casing Color
 SUBSILL : No Casing Subsill/Sillnose
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
 COATING : LOW E 366
 SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
 CERTIFIED : Impact Certified

SASH TYPE : Triple Sash
 GLAZING STOP : Interior Profiled Glazing Stops
 GRILLE TYPE : SDL Grille
 GRILLE COLOR : White Clad (Std)
 GRILLE STYLE : Colonial Grille
 GRILLE PATTERN : 2W3H Pattern
 VERTICAL SIZE : 3/4" (19mm)
 HORIZONTAL SIZE : 3/4" (19mm)
 EXT PROFILE : Ogee Exterior Profile
 INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Grille is a Standard Pattern
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 FLANGE : All Four Sides
 DRIPCAP : Snap On Dripcap
 PKG : Standard Packaging
 DRAWING# : 26075-07-00A
 APPROVAL# : 26075-07-00A
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : QM_ITEM : FFF
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

Line : 70.00	Model : 28AC	28 AWNING AND CASEMENT	(D)
Location: Stairs		Cubic Feet: 44.000	
Qty : 4.00	U/M : EA	List : 2743.00	Disc% : 23.25
		Net : 2,105.25	Total : 8,421.00

BUILD TYPE : Complete Unit
 UNIT STYLE : Casement Style
 UNIT TYPE : Traditional Operation
 OPERATION : Fixed
 ENHANCED DP : Enhanced Performance
 JAMB MOLDING : Standard Moldings
 FRAME WIDTH : 1200 MM 47 1/4"
 FRAME HEIGHT : 1200 MM 47 1/4"
 UNIT SHAPE : Rectangular (Or Square)
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 BRICKMOLD : No Exterior Casings Required
 BRICKMOLD FIN : No Casing Color
 SUBSILL : No Casing Subsill/Sillnose
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_5_366/B20-130/CLR_13.6SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 5 MM Glass Thickness
 HEAT STRENGTH : Heat Strengthened Lamination
 LAMI GLASS : 13.6MM SGP 5.7/.090/5.7
 COATING : LOW E 366
 PANE2HEAT : Heat Strengthened Laminated Glass

CERTIFIED : Impact Certified
 SASH TYPE : Triple Sash
 GLAZING STOP : Interior Profiled Glazing Stops
 GRILLE TYPE : SDL Grille
 GRILLE COLOR : White Clad (Std)
 GRILLE STYLE : Colonial Grille
 GRILLE PATTERN : 3W2H Pattern
 VERTICAL SIZE : 3/4" (19mm)
 HORIZONTAL SIZE : 3/4" (19mm)
 EXT PROFILE : Ogee Exterior Profile
 INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Grille is a Standard Pattern
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 FLANGE : All Four Sides
 DRIPCAP : Snap On Dripcap
 PKG : Standard Packaging
 DRAWING# : 26075-07-00A
 APPROVAL# : 26075-07-00A
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : QM_ITEM : HHH,KKK,LLL,YYY
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM

Line : 71.00	Model : 28AC	28 AWNING AND CASEMENT	(D)
Location: Bath 5		Cubic Feet: 6.000	
Qty : 1.00	U/M : EA	List : 1421.00	Disc% : 23.25 Net : 1,090.62 Total : 1,090.62

BUILD TYPE : Complete Unit
 UNIT STYLE : Casement Style
 UNIT TYPE : Traditional Operation
 OPERATION : Fixed
 ENHANCED DP : Enhanced Performance
 JAMB MOLDING : Standard Moldings
 FRAME WIDTH : 500 MM 19 11/16"
 FRAME HEIGHT : 1400 MM 55 1/8"
 UNIT SHAPE : Rectangular (Or Square)
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 BRICKMOLD : No Exterior Casings Required
 BRICKMOLD FIN : No Casing Color
 SUBSILL : No Casing Subsill/Sillnose
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
 COATING : LOW E 366
 SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
 CERTIFIED : Impact Certified

SASH TYPE : Triple Sash
 GLAZING STOP : Interior Profiled Glazing Stops
 GRILLE TYPE : SDL Grille
 GRILLE COLOR : White Clad (Std)
 GRILLE STYLE : Colonial Grille
 GRILLE PATTERN : 2W3H Pattern
 VERTICAL SIZE : 3/4" (19mm)
 HORIZONTAL SIZE : 3/4" (19mm)
 EXT PROFILE : Ogee Exterior Profile
 INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Grille is a Standard Pattern
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 FLANGE : All Four Sides
 DRIPCAP : Snap On Dripcap
 PKG : Standard Packaging
 DRAWING# : 26075-07-00A
 APPROVAL# : 26075-07-00A
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : QM_ITEM : MMM
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

Line : 74.00	Model : 28AC	28 AWNING AND CASEMENT	(D)
Location: Guest Living		Cubic Feet: 26.000	
Qty : 2.00	U/M : EA	List : 2915.00	Disc% : 23.25 Net : 2,237.26 Total : 4,474.52

BUILD TYPE : Complete Unit
 UNIT STYLE : Casement Style
 UNIT TYPE : Traditional Operation
 OPERATION : Fixed
 ENHANCED DP : Enhanced Performance
 JAMB MOLDING : Standard Moldings
 FRAME WIDTH : 750 MM 29 9/16"
 FRAME HEIGHT : 2100 MM 82 11/16"
 UNIT SHAPE : Rectangular (Or Square)
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 BRICKMOLD : No Exterior Casings Required
 BRICKMOLD FIN : No Casing Color
 SUBSILL : No Casing Subsill/Sillnose
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
 COATING : LOW E 366

SASH TYPE : Triple Sash
 GLAZING STOP : Interior Profiled Glazing Stops
 GRILLE TYPE : SDL Grille
 GRILLE COLOR : White Clad (Std)
 GRILLE STYLE : Colonial Grille
 GRILLE PATTERN : 2W3H Pattern
 VERTICAL SIZE : 3/4" (19mm)
 HORIZONTAL SIZE : 3/4" (19mm)
 EXT PROFILE : Ogee Exterior Profile
 INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Grille is a Standard Pattern
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 FLANGE : All Four Sides
 DRIPCAP : Snap On Dripcap
 PKG : Standard Packaging
 DRAWING# : 26075-07-00A
 APPROVAL# : 26075-07-00A
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : QM_ITEM : RRR.1

SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
 CERTIFIED : Not Impact Certified

MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

Line : 75.00	Model : 28AC	28 AWNING AND CASEMENT		(D)
Location: _Guest Living		Cubic Feet: 23.000		
Qty : 1.00	U/M : EA	List : 5588.00	Disc% : 23.25	Net : 4,288.79 Total : 4,288.79

BUILD TYPE : Complete Unit	HEAT STRENGTH : Heat Strengthened Lamination
UNIT STYLE : Casement Style	LAMI GLASS : 13.6MM SGP 5.7/.090/5.7
UNIT TYPE : Traditional Operation	COATING : LOW E 366
OPERATION : Fixed	PANE2HEAT : Heat Strengthened Laminated Glass
ENHANCED DP : Enhanced Performance	SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
JAMB MOLDING : Standard Moldings	CERTIFIED : Impact Certified
FRAME WIDTH : 1600 MM	SASH TYPE : Triple Sash
FRAME HEIGHT : 2100 MM	GLAZING STOP : Interior Profiled Glazing Stops
UNIT SHAPE : Rectangular (Or Square)	HARDWARE COLOR : No Hardware Color
SPECIES : Douglas Fir	LOCK : No Locks
FRAME FINISH : White Clad (Std)	SCREEN TYPE : No Screen
SASH FINISH : Sash Color Matches Frame Color	FLANGE : All Four Sides
INT FRAME FIN : Primed	DRIPCAP : Snap On Dripcap
INT SASH FIN : Primed	PKG : Standard Packaging
JAMB : 116 MM	DRAWING# : 26075-07-00A
BRICKMOLD : No Exterior Casings Required	APPROVAL# : 26075-07-00A
BRICKMOLD FIN : No Casing Color	QUALITY INSPECT : QC must Inspect Prior to PKG
SUBSILL : No Casing Subsill/Sillnose	WATER TEST : Water Tested in the Field
GLAZING : Stormforce Series IP D-Missile	FRMNOSE : Standard
GLZ CONFIG : CLR_5_366/B20-130/CLR_13.6SGP_NOC	MIDCMT : QM_ITEM : RRR.2
GLASS TINT : Clear Glass	MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
GLASS THICKNESS : 5 MM Glass Thickness	

Line : 76.00	Model : 28AC	28 AWNING AND CASEMENT		(D)
Location: _Guest Bath		Cubic Feet: 8.000		
Qty : 1.00	U/M : EA	List : 6483.00	Disc% : 23.25	Net : 4,975.70 Total : 4,975.70

BUILD TYPE : Complete Unit	SASH TYPE : Triple Sash
UNIT STYLE : Casement Style	GLAZING STOP : Interior Profiled Glazing Stops
UNIT TYPE : Traditional Operation	GRILLE TYPE : SDL Grille
OPERATION : Fixed	GRILLE COLOR : White Clad (Std)
ENHANCED DP : Enhanced Performance	GRILLE STYLE : Colonial Grille
JAMB MOLDING : Standard Moldings	GRILLE PATTERN : 2W3H Pattern
FRAME WIDTH : 600 MM	VERTICAL SIZE : 3/4" (19mm)
FRAME HEIGHT : 1500 MM	HORIZONTAL SIZE : 3/4" (19mm)
UNIT SHAPE : Ellipse	EXT PROFILE : Ogee Exterior Profile
LOWER HEIGHT : 1271 MM	INT PROFILE : Ogee Interior Profile
SPECIES : Douglas Fir	GRILLE SPACER : 1 Airspace With Shadow Bars
FRAME FINISH : White Clad (Std)	GRL SHADOW BAR : Deep Shadow Bar
SASH FINISH : Sash Color Matches Frame Color	GRILLE STD PATT : Grille is a Standard Pattern
INT FRAME FIN : Primed	HARDWARE COLOR : No Hardware Color
INT SASH FIN : Primed	LOCK : No Locks
INT GRILLE FIN : Primed	SCREEN TYPE : No Screen
JAMB : 116 MM	FLANGE : Left, Right, Sill
BRICKMOLD : No Exterior Casings Required	DRIPCAP : Integral Dripcap
BRICKMOLD FIN : No Casing Color	PKG : Standard Packaging
SUBSILL : No Casing Subsill/Sillnose	DRAWING# : 31689-02-00A
GLAZING : Stormforce Series IP D-Missile	APPROVAL# : 31689-02-00A
GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC	ID# : 0001
GLASS TINT : Clear Glass	QUALITY INSPECT : QC must Inspect Prior to PKG
GLASS THICKNESS : 3 MM Glass Thickness	WATER TEST : Water Tested in the Field
LAMI GLASS : 10.1MM SGP 3.9/.090/3.9	FRMNOSE : Standard
COATING : LOW E 366	MIDCMT : QM_ITEM : SSS
SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM	MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
CERTIFIED : Impact Certified	

*

Line : 83.00	Model : 28AC	28 AWNING AND CASEMENT	(D)
Location: Pool Bath		Cubic Feet: 5.000	
Qty : 1.00	U/M : EA	List : 1094.00	Disc% : 23.25
		Net : 839.65	Total : 839.65

BUILD TYPE : Complete Unit
 UNIT STYLE : Casement Style
 UNIT TYPE : Traditional Operation
 OPERATION : Fixed
 ENHANCED DP : Enhanced Performance
 JAMB MOLDING : Standard Moldings
 FRAME WIDTH : 500 MM 19 11/16"
 FRAME HEIGHT : 1000 MM 39 3/8"
 UNIT SHAPE : Rectangular (Or Square)
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 BRICKMOLD : No Exterior Casings Required
 BRICKMOLD FIN : No Casing Color
 SUBSILL : No Casing Subsill/Sillnose
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
 COATING : LOW E 366
 SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
 CERTIFIED : Impact Certified

SASH TYPE : Triple Sash
 GLAZING STOP : Interior Profiled Glazing Stops
 GRILLE TYPE : SDL Grille
 GRILLE COLOR : White Clad (Std)
 GRILLE STYLE : Colonial Grille
 GRILLE PATTERN : 2W2H Pattern
 VERTICAL SIZE : 3/4" (19mm)
 HORIZONTAL SIZE : 3/4" (19mm)
 EXT PROFILE : Ogee Exterior Profile
 INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Grille Is a Standard Pattern
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 FLANGE : All Four Sides
 DRIPCAP : Snap On Dripcap
 PKG : Standard Packaging
 DRAWING# : 26075-07-00A
 APPROVAL# : 26075-07-00A
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : QM_ITEM : WWW
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

Line : 84.00	Model : 28AC	28 AWNING AND CASEMENT	(D)
Location: Upper Front EI		Cubic Feet: 11.000	
Qty : 1.00	U/M : EA	List : 11929.00	Disc% : 23.25
		Net : 9,155.51	Total : 9,155.51

BUILD TYPE : Complete Unit
 UNIT STYLE : Casement Style
 UNIT TYPE : Traditional Operation
 OPERATION : Fixed
 ENHANCED DP : Enhanced Performance
 JAMB MOLDING : Standard Moldings
 FRAME WIDTH : 2083 MM 82"
 FRAME HEIGHT : 860 MM 26"
 UNIT SHAPE : Ellipse
 LOWER HEIGHT : 117 MM 4 5/8"
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 BRICKMOLD : No Exterior Casings Required
 BRICKMOLD FIN : No Casing Color
 SUBSILL : No Casing Subsill/Sillnose
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
 COATING : LOW E 366
 SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM

SASH TYPE : Triple Sash
 GLAZING STOP : Interior Profiled Glazing Stops
 GRILLE TYPE : SDL Grille
 GRILLE COLOR : White Clad (Std)
 GRILLE STYLE : SD:CUSTOM GRILLE AS PER 31689-04-00A
 GRILLE PATTERN : SD:CUSTOM GRILLE AS PER 31689-04-00A
 VERTICAL SIZE : 3/4" (19mm)
 HORIZONTAL SIZE : 3/4" (19mm)
 EXT PROFILE : Ogee Exterior Profile
 INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Unique Measurements, see Drawing
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 FLANGE : Left, Right, Sill
 DRIPCAP : Integral Dripcap
 PKG : Standard Packaging
 DRAWING# : 31689-04-00A
 APPROVAL# : 31689-04-00A
 ID# : 0001,0002,0003
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : QM_ITEM : XXX
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

*

CERTIFIED : Impact Certified

Line : 89.00	Model : WDHD	WINDOW HARDWARE		(D)
Location:		Cubic Feet:		
Qty : 1.00	U/M : EA	List :	Disc% : 23.25 Net : .00	Total : .00

Line : 91.00	Model : 49CM	COMPOSITE UNIT MODEL		(D)
Location: Two Car Garage		Cubic Feet: 42.000		
Qty : 3.00	U/M : EA	List :	3767.01 Disc% : 23.25 Net : 2,891.18	Total : 8,673.54

CONFIGURATION : Unit / Unit	BRICKMOLD FIN : No Casing Color
SUB 1 : 28AC CAS RCT 0900X0600 F //	BRICKMOLD FIN : No Casing Color
SUB 2 : 28AC CAS RCT 0900X1400 F	DRIPCAP : Snap On Dripcap
FRAME WIDTH : 900 MM 35 7/16"	FLANGE : All Four Sides
FRAME HEIGHT : 2000 MM 78 3/4"	DRAWING# : 31689-06-00A
SPECIES : Douglas Fir	APPROVAL# : 31689-06-00A
JAMB : 116 MM 4 9/16"	PACKAGING : Standard Packaging
UNIT SHAPE : Rectangular (Or Square)	QUALITY INSPECT : QC must Inspect Prior to PKG
FRAME FINISH : White Clad (Std)	WATER TEST : Water Tested in the Field
INT FRAME FIN : Primed	FRMNOSE : Standard
BRICKMOLD : No Exterior Casings Required	MIDCMT : CF:28AC F 900MM X 600MM //28AC F 900MM X 1400 F
CBSILLATTCH : No Casing Subsill/Sillnose	MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

Line : 92.00	Model : 28AC	28 AWNING AND CASEMENT	
PLine : 91.00	Qty : 3.00	U/M : EA	

BUILD TYPE : Complete Unit	CERTIFIED : Impact Certified
UNIT STYLE : Casement Style	SASH TYPE : Triple Sash
UNIT TYPE : Traditional Operation	GLAZING STOP : Interior Profiled Glazing Stops
OPERATION : Fixed	GRILLE TYPE : SDL Grille
ENHANCED DP : Enhanced Performance	GRILLE COLOR : White Clad (Std)
JAMB MOLDING : Standard Moldings	GRILLE STYLE : SD:CUSTOM GRILLE AS PER 31689-06-00A
FRAME WIDTH : 900 MM 35 7/16"	GRILLE PATTERN : SD:CUSTOM GRILLE AS PER 31689-06-00A
FRAME HEIGHT : 600 MM 23 5/8"	VERTICAL SIZE : 3/4" (19mm)
UNIT SHAPE : Rectangular (Or Square)	HORIZONTAL SIZE : 3/4" (19mm)
SPECIES : Douglas Fir	EXT PROFILE : Ogee Exterior Profile
FRAME FINISH : White Clad (Std)	INT PROFILE : Ogee Interior Profile
SASH FINISH : Sash Color Matches Frame Color	GRILLE SPACER : 1 Airspace With Shadow Bars
INT FRAME FIN : Primed	GRL SHADOW BAR : Deep Shadow Bar
INT SASH FIN : Primed	GRILLE STD PATT : Unique Measurements, see Drawing
INT GRILLE FIN : Primed	HARDWARE COLOR : No Hardware Color
JAMB : 116 MM 4 9/16"	LOCK : No Locks
GLAZING : Stormforce Series IP D-Missile	SCREEN TYPE : No Screen
GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC	QUALITY INSPECT : QC must Inspect Prior to PKG
GLASS TINT : Clear Glass	WATER TEST : Water Tested In the Field
GLASS THICKNESS : 3 MM Glass Thickness	FRMNOSE : Standard
LAMI GLASS : 10.1MM SGP 3.9/.090/3.9	MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
COATING : LOW E 366	MIDCMT : CF:28AC F 900MM X 600MM //28AC F 900MM X 1400 F
SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM	

Line : 93.00 Model : 28AC 28 AWNING AND CASEMENT
 PLine : 91.00 Qty : 3.00 U/M : EA

BUILD TYPE	: Complete Unit	CERTIFIED	: Impact Certified
UNIT STYLE	: Casement Style	SASH TYPE	: Triple Sash
UNIT TYPE	: Traditional Operation	GLAZING STOP	: Interior Profiled Glazing Stops
OPERATION	: Fixed	GRILLE TYPE	: SDL Grille
ENHANCED DP	: Enhanced Performance	GRILLE COLOR	: White Clad (Std)
JAMB MOLDING	: Standard Moldings	GRILLE STYLE	: Colonial Grille
FRAME WIDTH	: 900 MM 35 7/16"	GRILLE PATTERN	: 2W2H Pattern
FRAME HEIGHT	: 1400 MM 65 1/8"	VERTICAL SIZE	: 3/4" (19mm)
UNIT SHAPE	: Rectangular (Or Square)	HORIZONTAL SIZE	: 3/4" (19mm)
SPECIES	: Douglas Fir	EXT PROFILE	: Ogee Exterior Profile
FRAME FINISH	: White Clad (Std)	INT PROFILE	: Ogee Interior Profile
SASH FINISH	: Sash Color Matches Frame Color	GRILLE SPACER	: 1 Airspace With Shadow Bars
INT FRAME FIN	: Primed	GRL SHADOW BAR	: Deep Shadow Bar
INT SASH FIN	: Primed	GRILLE STD PATT	: Grille is a Standard Pattern
INT GRILLE FIN	: Primed	HARDWARE COLOR	: No Hardware Color
JAMB	: 116 MM 4 9/16"	LOCK	: No Locks
GLAZING	: Stormforce Series IP D-Missile	SCREEN TYPE	: No Screen
GLZ CONFIG	: CLR_3_366/B20-130/CLR_10.1SGP_NOC	QUALITY INSPECT	: QC must Inspect Prior to PKG
GLASS TINT	: Clear Glass	WATER TEST	: Water Tested in the Field
GLASS THICKNESS	: 3 MM Glass Thickness	FRMNOSE	: Standard
LAMI GLASS	: 10.1MM SGP 3.9/.090/3.9	MIDCMT	: AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
COATING	: LOW E 366	MIDCMT	: CF:28AC F 900MM X 600MM //28AC F 900MM X 1400 F
SPACER FINISH	: BRZ Aluminum(20)Spacer Bar 13MM		

Line : 94.00 Model : 49CM COMPOSITE UNIT MODEL (D)
 Location: _Bedroom 2 Cubic Feet: 26.000
 Qty : 1.00 U/M : EA List : 13064.01 Disc% : 23.25 Net : 10,026.63 Total : 10,026.63

CONFIGURATION	: Unit - Unit / Unit - Unit	BRICKMOLD FIN	: No Casing Color
SUB 1	: 28AC CAS ELP 0900X0562 F -	BRICKMOLD FIN	: No Casing Color
SUB 2	: 28AC CAS ELP 0900X0562 F //	DRIPCAP	: Snap On Dripcap
SUB 3	: 28AC CAS RCT 0900X1400 F -	FLANGE	: All Four Sides
SUB 4	: 28AC CAS RCT 0900X1400 F	DRAWING#	: 31689-05-00A
FRAME WIDTH	: 1800 MM 70 7/8"	APPROVAL#	: 31689-05-00A
FRAME HEIGHT	: 1968 MM 77 1/2"	SPECIAL INSTR	: C/W 1/4"x4" STEEL BETWEEN SHAPED UNITS & CASEMENT
RADIUS	: 2195 MM 86 7/16"	PACKAGING	: Standard Packaging
SPECIES	: Douglas Fir	QUALITY INSPECT	: QC must Inspect Prior to PKG
JAMB	: 116 MM 4 9/16"	WATER TEST	: Water Tested in the Field
UNIT SHAPE	: Ellipse	FRMNOSE	: Standard
FRAME FINISH	: White Clad (Std)	MIDCMT	: CF:28AC EL 0906-28AC EL 0906//HORIZ HIDDEN STEEL//
INT FRAME FIN	: Primed	MIDCMT	: CF:28AC F 0914 -28AC F 0914
BRICKMOLD	: No Exterior Casings Required	MIDCMT	: AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
CBSILLATTCH	: No Casing Subsill/Sillnose		

Line : 95.00 Model : 28AC 28 AWNING AND CASEMENT
 PLine : 94.00 Qty : 1.00 U/M : EA

BUILD TYPE	: Complete Unit	CERTIFIED	: Impact Certified
UNIT STYLE	: Casement Style	SASH TYPE	: Triple Sash
UNIT TYPE	: Traditional Operation	GLAZING STOP	: Interior Profiled Glazing Stops
OPERATION	: Fixed	GRILLE TYPE	: SDL Grille
ENHANCED DP	: Enhanced Performance	GRILLE COLOR	: White Clad (Std)
JAMB MOLDING	: Standard Moldings	GRILLE STYLE	: Colonial Grille
FRAME WIDTH	: 900 MM 35 7/16"	GRILLE PATTERN	: 2W1H Pattern
FRAME HEIGHT	: 662 MM 22 1/8"	VERTICAL SIZE	: 3/4" (19mm)
UNIT SHAPE	: Ellipse	HORIZONTAL SIZE	: Not Required
LOWER HEIGHT	: 175 MM 6 7/8"	EXT PROFILE	: Ogee Exterior Profile
SPECIES	: Douglas Fir	INT PROFILE	: Ogee Interior Profile
FRAME FINISH	: White Clad (Std)	GRILLE SPACER	: 1 Airspace With Shadow Bars

SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
 COATING : LOW E 366
 SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
 CERTIFIED : Impact Certified

GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Grille is a Standard Pattern
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 SPECIAL INSTR : SPCL
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
 MIDCMT : CF:28AC EL 0906-28AC EL 0906//HORIZ HIDDEN STEEL//
 MIDCMT : CF:28AC F 0914 -28AC F 0914

Line : 96.00 Model : 28AC 28 AWNING AND CASEMENT
 PLine : 94.00 Qty : 1.00 U/M : EA

BUILD TYPE : Complete Unit
 UNIT STYLE : Casement Style
 UNIT TYPE : Traditional Operation
 OPERATION : Fixed
 ENHANCED DP : Enhanced Performance
 JAMB MOLDING : Standard Moldings
 FRAME WIDTH : 900 MM 35 7/16"
 FRAME HEIGHT : 562 MM 22 1/8"
 UNIT SHAPE : Ellipse
 LOWER HEIGHT : 175 MM 6 7/8"
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
 COATING : LOW E 366
 SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM

CERTIFIED : Impact Certified
 SASH TYPE : Triple Sash
 GLAZING STOP : Interior Profiled Glazing Stops
 GRILLE TYPE : SDL Grille
 GRILLE COLOR : White Clad (Std)
 GRILLE STYLE : Colonial Grille
 GRILLE PATTERN : 2W1H Pattern
 VERTICAL SIZE : 3/4" (19mm)
 HORIZONTAL SIZE : Not Required
 EXT PROFILE : Ogee Exterior Profile
 INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Grille is a Standard Pattern
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 SPECIAL INSTR : SPCL
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
 MIDCMT : CF:28AC EL 0906-28AC EL 0906//HORIZ HIDDEN STEEL//
 MIDCMT : CF:28AC F 0914 -28AC F 0914

Line : 97.00 Model : 28AC 28 AWNING AND CASEMENT
 PLine : 94.00 Qty : 1.00 U/M : EA

BUILD TYPE : Complete Unit
 UNIT STYLE : Casement Style
 UNIT TYPE : Traditional Operation
 OPERATION : Fixed
 ENHANCED DP : Enhanced Performance
 JAMB MOLDING : Standard Moldings
 FRAME WIDTH : 900 MM 35 7/16"
 FRAME HEIGHT : 1400 MM 55 1/8"
 UNIT SHAPE : Rectangular (Or Square)
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC

SASH TYPE : Triple Sash
 GLAZING STOP : Interior Profiled Glazing Stops
 GRILLE TYPE : SDL Grille
 GRILLE COLOR : White Clad (Std)
 GRILLE STYLE : Colonial Grille
 GRILLE PATTERN : 2W2H Pattern
 VERTICAL SIZE : 3/4" (19mm)
 HORIZONTAL SIZE : 3/4" (19mm)
 EXT PROFILE : Ogee Exterior Profile
 INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Grille is a Standard Pattern
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 SPECIAL INSTR : SPCL
 QUALITY INSPECT : QC must Inspect Prior to PKG

GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
 COATING : LOW E 366
 SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
 CERTIFIED : Impact Certified

WATER TEST : Water Tested In the Field
 FRMNOSE : Standard
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
 MIDCMT : CF:28AC EL 0906-28AC EL 0906//HORIZ HIDDEN STEEL//
 MIDCMT : CF:28AC F 0914 -28AC F 0914

Line : 98.00 Model : 28AC 28 AWNING AND CASEMENT
 PLine : 94.00 Qty : 1.00 U/M : EA

BUILD TYPE : Complete Unit
 UNIT STYLE : Casement Style
 UNIT TYPE : Traditional Operation
 OPERATION : Fixed
 ENHANCED DP : Enhanced Performance
 JAMB MOLDING : Standard Moldings
 FRAME WIDTH : 900 MM 35 7/16"
 FRAME HEIGHT : 1400 MM 55 1/8"
 UNIT SHAPE : Rectangular (Or Square)
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
 COATING : LOW E 366
 SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
 CERTIFIED : Impact Certified

SASH TYPE : Triple Sash
 GLAZING STOP : Interior Profiled Glazing Stops
 GRILLE TYPE : SDL Grille
 GRILLE COLOR : White Clad (Std)
 GRILLE STYLE : Colonial Grille
 GRILLE PATTERN : 2W2H Pattern
 VERTICAL SIZE : 3/4" (19mm)
 HORIZONTAL SIZE : 3/4" (19mm)
 EXT PROFILE : Ogee Exterior Profile
 INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Grille is a Standard Pattern
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 SPECIAL INSTR : SPCL
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
 MIDCMT : CF:28AC EL 0906-28AC EL 0906//HORIZ HIDDEN STEEL//
 MIDCMT : CF:28AC F 0914 -28AC F 0914

Line : 99.00 Model : 49CM COMPOSITE UNIT MODEL (D)
 Location: Two Car Garage Cubic Feet: 26.000
 Qty : 1.00 U/M : EA List : 7358.01 Disc% : 23.25 Net : 5,647.27 Total : 5,647.27

CONFIGURATION : Unit - Unit / Unit - Unit
 SUB 1 : 28AC CAS RCT 0900X0600 F -
 SUB 2 : 28AC CAS RCT 0900X0600 F //
 SUB 3 : 28AC CAS RCT 0900X1400 F -
 SUB 4 : 28AC CAS RCT 0900X1400 F
 FRAME WIDTH : 1800 MM 70 7/8"
 FRAME HEIGHT : 2006 MM 79"
 SPECIES : Douglas Fir
 JAMB : 116 MM 4 9/16"
 UNIT SHAPE : Rectangular (Or Square)
 FRAME FINISH : White Clad (Std)
 INT FRAME FIN : Primed
 BRICKMOLD : No Exterior Casings Required
 CBSILLATTCH : No Casing SubSill/Sillnose

BRICKMOLD FIN : No Casing Color
 BRICKMOLD FIN : No Casing Color
 DRIPCAP : No Dripcap Required
 FLANGE : All Four Sides
 DRAWING# : 31689-07-00A
 APPROVAL# : 31689-07-00A
 SPECIAL INSTR : CW 1/4"X4"STEEL BETWEEN UPPER&LOWER CASEMENTS
 PACKAGING : Standard Packaging
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested In the Field
 FRMNOSE : Standard
 MIDCMT : CF:28AC F 0906-28AC F 0906//HORIZ HIDDEN STEEL//
 MIDCMT : CF:28AC F 0914 -28AC F 0914
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

Line : 100.00 Model : 28AC 28 AWNING AND CASEMENT
 PLine : 99.00 Qty : 1.00 U/M : EA

BUILD TYPE	: Complete Unit	SASH TYPE	: Triple Sash
UNIT STYLE	: Casement Style	GLAZING STOP	: Interior Profiled Glazing Stops
UNIT TYPE	: Traditional Operation	GRILLE TYPE	: SDL Grille
OPERATION	: Fixed	GRILLE COLOR	: White Clad (Std)
ENHANCED DP	: Enhanced Performance	GRILLE STYLE	: SD:CUSTOM GRILLE AS PER 31689-07-00A
JAMB MOLDING	: Standard Moldings	GRILLE PATTERN	: SD:CUSTOM GRILLE AS PER 31689-07-00A
FRAME WIDTH	: 900 MM 35 7/16"	VERTICAL SIZE	: 3/4" (19mm)
FRAME HEIGHT	: 600 MM 23 5/8"	HORIZONTAL SIZE	: 3/4" (19mm)
UNIT SHAPE	: Rectangular (Or Square)	EXT PROFILE	: Ogee Exterior Profile
SPECIES	: Douglas Fir	INT PROFILE	: Ogee Interior Profile
FRAME FINISH	: White Clad (Std)	GRILLE SPACER	: 1 Airspace With Shadow Bars
SASH FINISH	: Sash Color Matches Frame Color	GRL SHADOW BAR	: Deep Shadow Bar
INT FRAME FIN	: Primed	GRILLE STD PATT	: Unique Measurements, see Drawing
INT SASH FIN	: Primed	HARDWARE COLOR	: No Hardware Color
INT GRILLE FIN	: Primed	LOCK	: No Locks
JAMB	: 116 MM 4 9/16"	SCREEN TYPE	: No Screen
GLAZING	: Stormforce Series IP D-Missile	SPECIAL INSTR	: SPCL
GLZ CONFIG	: CLR_3_366/B20-130/CLR_10.1SGP_NOC	QUALITY INSPECT	: QC must Inspect Prior to PKG
GLASS TINT	: Clear Glass	WATER TEST	: Water Tested in the Field
GLASS THICKNESS	: 3 MM Glass Thickness	FRMNOSE	: Standard
LAMI GLASS	: 10.1MM SGP 3.9/.090/3.9	MIDCMT	: AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
COATING	: LOW E 366	MIDCMT	: CF:28AC F 0906-28AC F 0906//HORIZ HIDDEN STEEL//
SPACER FINISH	: BRZ Aluminum(20)Spacer Bar 13MM	MIDCMT	: CF:28AC F 0914 -28AC F 0914
CERTIFIED	: Impact Certified		

Line : 101.00 Model : 28AC 28 AWNING AND CASEMENT
 PLine : 99.00 Qty : 1.00 U/M : EA

BUILD TYPE	: Complete Unit	SASH TYPE	: Triple Sash
UNIT STYLE	: Casement Style	GLAZING STOP	: Interior Profiled Glazing Stops
UNIT TYPE	: Traditional Operation	GRILLE TYPE	: SDL Grille
OPERATION	: Fixed	GRILLE COLOR	: White Clad (Std)
ENHANCED DP	: Enhanced Performance	GRILLE STYLE	: SD:CUSTOM GRILLE AS PER 31689-07-00A
JAMB MOLDING	: Standard Moldings	GRILLE PATTERN	: SD:CUSTOM GRILLE AS PER 31689-07-00A
FRAME WIDTH	: 900 MM 35 7/16"	VERTICAL SIZE	: 3/4" (19mm)
FRAME HEIGHT	: 600 MM 23 5/8"	HORIZONTAL SIZE	: 3/4" (19mm)
UNIT SHAPE	: Rectangular (Or Square)	EXT PROFILE	: Ogee Exterior Profile
SPECIES	: Douglas Fir	INT PROFILE	: Ogee Interior Profile
FRAME FINISH	: White Clad (Std)	GRILLE SPACER	: 1 Airspace With Shadow Bars
SASH FINISH	: Sash Color Matches Frame Color	GRL SHADOW BAR	: Deep Shadow Bar
INT FRAME FIN	: Primed	GRILLE STD PATT	: Unique Measurements, see Drawing
INT SASH FIN	: Primed	HARDWARE COLOR	: No Hardware Color
INT GRILLE FIN	: Primed	LOCK	: No Locks
JAMB	: 116 MM 4 9/16"	SCREEN TYPE	: No Screen
GLAZING	: Stormforce Series IP D-Missile	SPECIAL INSTR	: SPCL
GLZ CONFIG	: CLR_3_366/B20-130/CLR_10.1SGP_NOC	QUALITY INSPECT	: QC must Inspect Prior to PKG
GLASS TINT	: Clear Glass	WATER TEST	: Water Tested in the Field
GLASS THICKNESS	: 3 MM Glass Thickness	FRMNOSE	: Standard
LAMI GLASS	: 10.1MM SGP 3.9/.090/3.9	MIDCMT	: AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
COATING	: LOW E 366	MIDCMT	: CF:28AC F 0906-28AC F 0906//HORIZ HIDDEN STEEL//
SPACER FINISH	: BRZ Aluminum(20)Spacer Bar 13MM	MIDCMT	: CF:28AC F 0914 -28AC F 0914
CERTIFIED	: Impact Certified		

Line : 102.00 Model : 28AC

28 AWNING AND CASEMENT

PLine : 99.00 Qty : 1.00

U/M : EA

BUILD TYPE : Complete Unit
UNIT STYLE : Casement Style
UNIT TYPE : Traditional Operation
OPERATION : Fixed
ENHANCED DP : Enhanced Performance
JAMB MOLDING : Standard Moldings
FRAME WIDTH : 900 MM 35 7/16"
FRAME HEIGHT : 1400 MM 55 1/8"
UNIT SHAPE : Rectangular (Or Square)
SPECIES : Douglas Fir
FRAME FINISH : White Clad (Std)
SASH FINISH : Sash Color Matches Frame Color
INT FRAME FIN : Primed
INT SASH FIN : Primed
INT GRILLE FIN : Primed
JAMB : 116 MM 4 9/16"
GLAZING : Stormforce Series IP D-Missile
GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
GLASS TINT : Clear Glass
GLASS THICKNESS : 3 MM Glass Thickness
LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
COATING : LOW E 366
SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
CERTIFIED : Impact Certified

SASH TYPE : Triple Sash
GLAZING STOP : Interior Profiled Glazing Stops
GRILLE TYPE : SDL Grille
GRILLE COLOR : White Clad (Std)
GRILLE STYLE : Colonial Grille
GRILLE PATTERN : 2W2H Pattern
VERTICAL SIZE : 3/4" (19mm)
HORIZONTAL SIZE : 3/4" (19mm)
EXT PROFILE : Ogee Exterior Profile
INT PROFILE : Ogee Interior Profile
GRILLE SPACER : 1 Airspace With Shadow Bars
GRL SHADOW BAR : Deep Shadow Bar
GRILLE STD PATT : Grille is a Standard Pattern
HARDWARE COLOR : No Hardware Color
LOCK : No Locks
SCREEN TYPE : No Screen
SPECIAL INSTR : SPCL
QUALITY INSPECT : QC must Inspect Prior to PKG
WATER TEST : Water Tested in the Field
FRMNOSE : Standard
MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
MIDCMT : CF:28AC F 0906-28AC F 0906//HORIZ HIDDEN STEEL//
MIDCMT : CF:28AC F 0914 -28AC F 0914

Line : 103.00 Model : 28AC

28 AWNING AND CASEMENT

PLine : 99.00 Qty : 1.00

U/M : EA

BUILD TYPE : Complete Unit
UNIT STYLE : Casement Style
UNIT TYPE : Traditional Operation
OPERATION : Fixed
ENHANCED DP : Enhanced Performance
JAMB MOLDING : Standard Moldings
FRAME WIDTH : 900 MM 35 7/16"
FRAME HEIGHT : 1400 MM 55 1/8"
UNIT SHAPE : Rectangular (Or Square)
SPECIES : Douglas Fir
FRAME FINISH : White Clad (Std)
SASH FINISH : Sash Color Matches Frame Color
INT FRAME FIN : Primed
INT SASH FIN : Primed
INT GRILLE FIN : Primed
JAMB : 116 MM 4 9/16"
GLAZING : Stormforce Series IP D-Missile
GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
GLASS TINT : Clear Glass
GLASS THICKNESS : 3 MM Glass Thickness
LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
COATING : LOW E 366
SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
CERTIFIED : Impact Certified

SASH TYPE : Triple Sash
GLAZING STOP : Interior Profiled Glazing Stops
GRILLE TYPE : SDL Grille
GRILLE COLOR : White Clad (Std)
GRILLE STYLE : Colonial Grille
GRILLE PATTERN : 2W2H Pattern
VERTICAL SIZE : 3/4" (19mm)
HORIZONTAL SIZE : 3/4" (19mm)
EXT PROFILE : Ogee Exterior Profile
INT PROFILE : Ogee Interior Profile
GRILLE SPACER : 1 Airspace With Shadow Bars
GRL SHADOW BAR : Deep Shadow Bar
GRILLE STD PATT : Grille is a Standard Pattern
HARDWARE COLOR : No Hardware Color
LOCK : No Locks
SCREEN TYPE : No Screen
SPECIAL INSTR : SPCL
QUALITY INSPECT : QC must Inspect Prior to PKG
WATER TEST : Water Tested in the Field
FRMNOSE : Standard
MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
MIDCMT : CF:28AC F 0906-28AC F 0906//HORIZ HIDDEN STEEL//
MIDCMT : CF:28AC F 0914 -28AC F 0914

*

Line : 104.00	Model : 49CM	COMPOSITE UNIT MODEL	(D)
Location: Bedroom 5		Cubic Feet: 26.000	
Qty : 1.00	U/M : EA	List : 13064.01 Disc% : 23.25 Net : 10,026.63	Total : 10,026.63

CONFIGURATION : Unit - Unit / Unit - Unit		BRICKMOLD FIN : No Casing Color	
SUB 1 : 28AC CAS ELP 0900X0562 F -		BRICKMOLD FIN : No Casing Color	
SUB 2 : 28AC CAS ELP 0900X0562 F //		DRIPCAP : Snap On Dripcap	
SUB 3 : 28AC CAS RCT 0900X1400 F -		FLANGE : All Four Sides	
SUB 4 : 28AC CAS RCT 0900X1400 F		DRAWING# : 31689-05-00A	
FRAME WIDTH : 1800 MM	70 7/8"	APPROVAL# : 31689-05-00A	
FRAME HEIGHT : 1968 MM	77 1/2"	SPECIAL INSTR : C/W 1/4"X4" STEEL BETWEEN SHAPED UNITS & CASEMENT	
RADIUS : 2195 MM	86 7/16"	PACKAGING : Standard Packaging	
SPECIES : Douglas Fir		QUALITY INSPECT : QC must Inspect Prior to PKG	
JAMB : 116 MM	4 9/16"	WATER TEST : Water Tested in the Field	
UNIT SHAPE : Ellipse		FRMNOSE : Standard	
FRAME FINISH : White Clad (Std)		MIDCMT : CF:28AC EL 0906-28AC EL 0906//HORIZ HIDDEN STEEL//	
INT FRAME FIN : Primed		MIDCMT : CF:28AC F 0914 -28AC F 0914	
BRICKMOLD : No Exterior Casings Required		MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**	
CBSILLATTCH : No Casing Subsill/Sillnose			

Line : 105.00	Model : 28AC	28 AWNING AND CASEMENT	
PLine : 104.00	Qty : 1.00	U/M : EA	

BUILD TYPE : Complete Unit		CERTIFIED : Impact Certified	
UNIT STYLE : Casement Style		SASH TYPE : Triple Sash	
UNIT TYPE : Traditional Operation		GLAZING STOP : Interior Profiled Glazing Stops	
OPERATION : Fixed		GRILLE TYPE : SDL Grille	
ENHANCED DP : Enhanced Performance		GRILLE COLOR : White Clad (Std)	
JAMB MOLDING : Standard Moldings		GRILLE STYLE : Colonial Grille	
FRAME WIDTH : 900 MM	35 7/16"	GRILLE PATTERN : 2W1H Pattern	
FRAME HEIGHT : 562 MM	22 1/8"	VERTICAL SIZE : 3/4" (19mm)	
UNIT SHAPE : Ellipse		HORIZONTAL SIZE : Not Required	
LOWER HEIGHT : 175 MM	6 7/8"	EXT PROFILE : Ogee Exterior Profile	
SPECIES : Douglas Fir		INT PROFILE : Ogee Interior Profile	
FRAME FINISH : White Clad (Std)		GRILLE SPACER : 1 Airspace With Shadow Bars	
SASH FINISH : Sash Color Matches Frame Color		GRL SHADOW BAR : Deep Shadow Bar	
INT FRAME FIN : Primed		GRILLE STD PATT : Grille is a Standard Pattern	
INT SASH FIN : Primed		HARDWARE COLOR : No Hardware Color	
INT GRILLE FIN : Primed		LOCK : No Locks	
JAMB : 116 MM	4 9/16"	SCREEN TYPE : No Screen	
GLAZING : Stormforce Series IP D-Missile		SPECIAL INSTR : SPCL	
GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC		QUALITY INSPECT : QC must Inspect Prior to PKG	
GLASS TINT : Clear Glass		WATER TEST : Water Tested in the Field	
GLASS THICKNESS : 3 MM Glass Thickness		FRMNOSE : Standard	
LAMI GLASS : 10.1MM SGP 3.9/.090/3.9		MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**	
COATING : LOW E 366		MIDCMT : CF:28AC EL 0906-28AC EL 0906//HORIZ HIDDEN STEEL//	
SPACER FINISH : BR2 Aluminum(20)Spacer Bar 13MM		MIDCMT : CF:28AC F 0914 -28AC F 0914	

Line : 106.00	Model : 28AC	28 AWNING AND CASEMENT	
PLine : 104.00	Qty : 1.00	U/M : EA	

BUILD TYPE : Complete Unit		CERTIFIED : Impact Certified	
UNIT STYLE : Casement Style		SASH TYPE : Triple Sash	
UNIT TYPE : Traditional Operation		GLAZING STOP : Interior Profiled Glazing Stops	
OPERATION : Fixed		GRILLE TYPE : SDL Grille	
ENHANCED DP : Enhanced Performance		GRILLE COLOR : White Clad (Std)	
JAMB MOLDING : Standard Moldings		GRILLE STYLE : Colonial Grille	
FRAME WIDTH : 900 MM	35 7/16"	GRILLE PATTERN : 2W1H Pattern	
FRAME HEIGHT : 562 MM	22 1/8"	VERTICAL SIZE : 3/4" (19mm)	
UNIT SHAPE : Ellipse		HORIZONTAL SIZE : Not Required	
LOWER HEIGHT : 175 MM	6 7/8"	EXT PROFILE : Ogee Exterior Profile	

*

SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
 COATING : LOW E 366
 SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
 CERTIFIED : Impact Certified

INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Grille is a Standard Pattern
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 SPECIAL INSTR : SPCL
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
 MIDCMT : CF:28AC EL 0906-28AC EL 0906//HORIZ HIDDEN STEEL//
 MIDCMT : CF:28AC F 0914 -28AC F 0914

Line : 107.00 Model : 28AC 28 AWNING AND CASEMENT
 PLine : 104.00 Qty : 1.00 U/M : EA

BUILD TYPE : Complete Unit
 UNIT STYLE : Casement Style
 UNIT TYPE : Traditional Operation
 OPERATION : Fixed
 ENHANCED DP : Enhanced Performance
 JAMB MOLDING : Standard Moldings
 FRAME WIDTH : 900 MM 35 7/16"
 FRAME HEIGHT : 1400 MM 55 1/8"
 UNIT SHAPE : Rectangular (Or Square)
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
 COATING : LOW E 366
 SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
 CERTIFIED : Impact Certified

SASH TYPE : Triple Sash
 GLAZING STOP : Interior Profiled Glazing Stops
 GRILLE TYPE : SDL Grille
 GRILLE COLOR : White Clad (Std)
 GRILLE STYLE : Colonial Grille
 GRILLE PATTERN : 2W2H Pattern
 VERTICAL SIZE : 3/4" (19mm)
 HORIZONTAL SIZE : 3/4" (19mm)
 EXT PROFILE : Ogee Exterior Profile
 INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Grille is a Standard Pattern
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 SPECIAL INSTR : SPCL
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
 MIDCMT : CF:28AC EL 0906-28AC EL 0906//HORIZ HIDDEN STEEL//
 MIDCMT : CF:28AC F 0914 -28AC F 0914

Line : 108.00 Model : 28AC 28 AWNING AND CASEMENT
 PLine : 104.00 Qty : 1.00 U/M : EA

BUILD TYPE : Complete Unit
 UNIT STYLE : Casement Style
 UNIT TYPE : Traditional Operation
 OPERATION : Fixed
 ENHANCED DP : Enhanced Performance
 JAMB MOLDING : Standard Moldings
 FRAME WIDTH : 900 MM 35 7/16"
 FRAME HEIGHT : 1400 MM 55 1/8"
 UNIT SHAPE : Rectangular (Or Square)
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 GLAZING : Stormforce Series IP D-Missile

SASH TYPE : Triple Sash
 GLAZING STOP : Interior Profiled Glazing Stops
 GRILLE TYPE : SDL Grille
 GRILLE COLOR : White Clad (Std)
 GRILLE STYLE : Colonial Grille
 GRILLE PATTERN : 2W2H Pattern
 VERTICAL SIZE : 3/4" (19mm)
 HORIZONTAL SIZE : 3/4" (19mm)
 EXT PROFILE : Ogee Exterior Profile
 INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Grille is a Standard Pattern
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 SPECIAL INSTR : SPCL

GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
 COATING : LOW E 366
 SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
 CERTIFIED : Impact Certified

QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
 MIDCMT : CF:28AC EL 0906-28AC EL 0906//HORIZ HIDDEN STEEL//
 MIDCMT : CF:28AC F 0914 -28AC F 0914

Line : 109.00	Model : 49CM	COMPOSITE UNIT MODEL		(D)
Location: _Bedroom 4		Cubic Feet: 26.000		
Qty : 1.00	U/M : EA	List : 13064.01	Disc% : 23.25	Net : 10,026.63 Total : 10,026.63

CONFIGURATION : Unit - Unit / Unit - Unit	CBSILLATTCH : No Casing Sill/Sillnose
SUB 1 : 28AC CAS ELP 0900X0562 F -	BRICKMOLD FIN : No Casing Color
SUB 2 : 28AC CAS ELP 0900X0562 F //	BRICKMOLD FIN : No Casing Color
SUB 3 : 28AC CAS RCT 0900X1400 F -	DRIPCAP : Snap On Dripcap
SUB 4 : 28AC CAS RCT 0900X1400 F	FLANGE : All Four Sides
FRAME WIDTH : 1800 MM 70 7/8"	DRAWING# : 31689-05-00A
FRAME HEIGHT : 1968 MM 77 1/2"	APPROVAL# : 31689-05-00A
RADIUS : 2195 MM 86 7/16"	SPECIAL INSTR : C/W 1/4"x4" STEEL BETWEEN SHAPED UNITS & CASEMENT
SPECIES : Douglas Fir	PACKAGING : Standard Packaging
JAMB : 116 MM 4 9/16"	QUALITY INSPECT : QC must Inspect Prior to PKG
UNIT SHAPE : Ellipse	WATER TEST : Water Tested in the Field
FRAME FINISH : White Clad (Std)	FRMNOSE : Standard
INT FRAME FIN : Primed	MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
BRICKMOLD : No Exterior Casings Required	

Line : 110.00 Model : 28AC 28 AWNING AND CASEMENT
 PLine : 109.00 Qty : 1.00 U/M : EA

BUILD TYPE : Complete Unit	SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
UNIT STYLE : Casement Style	CERTIFIED : Impact Certified
UNIT TYPE : Traditional Operation	SASH TYPE : Triple Sash
OPERATION : Fixed	GLAZING STOP : Interior Profiled Glazing Stops
ENHANCED DP : Enhanced Performance	GRILLE TYPE : SDL Grille
JAMB MOLDING : Standard Moldings	GRILLE COLOR : White Clad (Std)
FRAME WIDTH : 900 MM 35 7/16"	GRILLE STYLE : Colonial Grille
FRAME HEIGHT : 562 MM 22 1/8"	GRILLE PATTERN : 2W1H Pattern
UNIT SHAPE : Ellipse	VERTICAL SIZE : 3/4" (19mm)
LOWER HEIGHT : 175 MM 6 7/8"	HORIZONTAL SIZE : Not Required
SPECIES : Douglas Fir	EXT PROFILE : Ogee Exterior Profile
FRAME FINISH : White Clad (Std)	INT PROFILE : Ogee Interior Profile
SASH FINISH : Sash Color Matches Frame Color	GRILLE SPACER : 1 Airspace With Shadow Bars
INT FRAME FIN : Primed	GRL SHADOW BAR : Deep Shadow Bar
INT SASH FIN : Primed	GRILLE STD PATT : Grille is a Standard Pattern
INT GRILLE FIN : Primed	HARDWARE COLOR : No Hardware Color
JAMB : 116 MM 4 9/16"	LOCK : No Locks
GLAZING : Stormforce Series IP D-Missle	SCREEN TYPE : No Screen
GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC	SPECIAL INSTR : SPCL
GLASS TINT : Clear Glass	QUALITY INSPECT : QC must Inspect Prior to PKG
GLASS THICKNESS : 3 MM Glass Thickness	WATER TEST : Water Tested in the Field
LAMI GLASS : 10.1MM SGP 3.9/.090/3.9	FRMNOSE : Standard
COATING : LOW E 366	MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

Line : 111.00 Model : 28AC

28 AWNING AND CASEMENT

PLine : 109.00 Qty : 1.00

U/M : EA

BUILD TYPE : Complete Unit
UNIT STYLE : Casement Style
UNIT TYPE : Traditional Operation
OPERATION : Fixed
ENHANCED DP : Enhanced Performance
JAMB MOLDING : Standard Moldings
FRAME WIDTH : 900 MM 35 7/16"
FRAME HEIGHT : 562 MM 22 1/8"
UNIT SHAPE : Ellipse
LOWER HEIGHT : 175 MM 6 7/8"
SPECIES : Douglas Fir
FRAME FINISH : White Clad (Std)
SASH FINISH : Sash Color Matches Frame Color
INT FRAME FIN : Primed
INT SASH FIN : Primed
INT GRILLE FIN : Primed
JAMB : 116 MM 4 9/16"
GLAZING : Stormforce Series IP D-Missile
GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
GLASS TINT : Clear Glass
GLASS THICKNESS : 3 MM Glass Thickness
LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
COATING : LOW E 366

SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
CERTIFIED : Impact Certified
SASH TYPE : Triple Sash
GLAZING STOP : Interior Profiled Glazing Stops
GRILLE TYPE : SDL Grille
GRILLE COLOR : White Clad (Std)
GRILLE STYLE : Colonial Grille
GRILLE PATTERN : 2W1H Pattern
VERTICAL SIZE : 3/4" (19mm)
HORIZONTAL SIZE : Not Required
EXT PROFILE : Ogee Exterior Profile
INT PROFILE : Ogee Interior Profile
GRILLE SPACER : 1 Airspace With Shadow Bars
GRL SHADOW BAR : Deep Shadow Bar
GRILLE STD PATT : Grille is a Standard Pattern
HARDWARE COLOR : No Hardware Color
LOCK : No Locks
SCREEN TYPE : No Screen
SPECIAL INSTR : SPCL
QUALITY INSPECT : QC must Inspect Prior to PKG
WATER TEST : Water Tested in the Field
FRMNOSE : Standard
MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

Line : 112.00 Model : 28AC

28 AWNING AND CASEMENT

PLine : 109.00 Qty : 1.00

U/M : EA

BUILD TYPE : Complete Unit
UNIT STYLE : Casement Style
UNIT TYPE : Traditional Operation
OPERATION : Fixed
ENHANCED DP : Enhanced Performance
JAMB MOLDING : Standard Moldings
FRAME WIDTH : 900 MM 35 7/16"
FRAME HEIGHT : 1400 MM 55 1/8"
UNIT SHAPE : Rectangular (Or Square)
SPECIES : Douglas Fir
FRAME FINISH : White Clad (Std)
SASH FINISH : Sash Color Matches Frame Color
INT FRAME FIN : Primed
INT SASH FIN : Primed
INT GRILLE FIN : Primed
JAMB : 116 MM 4 9/16"
GLAZING : Stormforce Series IP D-Missile
GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
GLASS TINT : Clear Glass
GLASS THICKNESS : 3 MM Glass Thickness
LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
COATING : LOW E 366
SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM

CERTIFIED : Impact Certified
SASH TYPE : Triple Sash
GLAZING STOP : Interior Profiled Glazing Stops
GRILLE TYPE : SDL Grille
GRILLE COLOR : White Clad (Std)
GRILLE STYLE : Colonial Grille
GRILLE PATTERN : 2W2H Pattern
VERTICAL SIZE : 3/4" (19mm)
HORIZONTAL SIZE : 3/4" (19mm)
EXT PROFILE : Ogee Exterior Profile
INT PROFILE : Ogee Interior Profile
GRILLE SPACER : 1 Airspace With Shadow Bars
GRL SHADOW BAR : Deep Shadow Bar
GRILLE STD PATT : Grille is a Standard Pattern
HARDWARE COLOR : No Hardware Color
LOCK : No Locks
SCREEN TYPE : No Screen
SPECIAL INSTR : SPCL
QUALITY INSPECT : QC must Inspect Prior to PKG
WATER TEST : Water Tested in the Field
FRMNOSE : Standard
MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

Line : 113.00 Model : 28AC

28 AWNING AND CASEMENT

PLine : 109.00 Qty : 1.00

U/M : EA

BUILD TYPE : Complete Unit
 UNIT STYLE : Casement Style
 UNIT TYPE : Traditional Operation
 OPERATION : Fixed
 ENHANCED DP : Enhanced Performance
 JAMB MOLDING : Standard Moldings
 FRAME WIDTH : 900 MM 35 7/16"
 FRAME HEIGHT : 1400 MM 55 1/8"
 UNIT SHAPE : Rectangular (Or Square)
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/0.90/3.9
 COATING : LOW E 366
 SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM

CERTIFIED : Impact Certified
 SASH TYPE : Triple Sash
 GLAZING STOP : Interior Profiled Glazing Stops
 GRILLE TYPE : SDL Grille
 GRILLE COLOR : White Clad (Std)
 GRILLE STYLE : Colonial Grille
 GRILLE PATTERN : 2W2H Pattern
 VERTICAL SIZE : 3/4" (19mm)
 HORIZONTAL SIZE : 3/4" (19mm)
 EXT PROFILE : Ogee Exterior Profile
 INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Grille is a Standard Pattern
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 SPECIAL INSTR : SPCL
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

Line : 122.00

Model : 49CM

COMPOSITE UNIT MODEL

(D)

Location: Bunkroom

Cubic Feet: 13.000

Qty : 1.00

U/M : EA

List :

6013.01

Disc% : 23.25

Net :

4,614.99

Total : 4,614.99

CONFIGURATION : Unit / Unit
 SUB 1 : 28AC CAS ELP 0750X0914 F //
 SUB 2 : 28AC CAS RCT 0750X1200 R
 FRAME WIDTH : 750 MM 29 9/16"
 FRAME HEIGHT : 2115 MM 83 5/16"
 LOWER HEIGHT : 1878 MM 73 15/16"
 RADIUS : 612 MM 24 1/8"
 SPECIES : Douglas Fir
 JAMB : 116 MM 4 9/16"
 UNIT SHAPE : Ellipse
 FRAME FINISH : White Clad (Std)
 INT FRAME FIN : Primed
 BRICKMOLD : No Exterior Casings Required

CBSILLATTCH : No Casing Sill/Sillnose
 BRICKMOLD FIN : No Casing Color
 BRICKMOLD FIN : No Casing Color
 DRIPCAP : Snap On Dripcap
 FLANGE : All Four Sides
 DRAWING# : 31689-03-00A
 APPROVAL# : 31689-03-00A
 PACKAGING : Standard Packaging
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

Line : 123.00 Model : 28AC

28 AWNING AND CASEMENT

PLine : 122.00 Qty : 1.00

U/M : EA

BUILD TYPE : Complete Unit
 UNIT STYLE : Casement Style
 UNIT TYPE : Traditional Operation
 OPERATION : Fixed
 ENHANCED DP : Enhanced Performance
 JAMB MOLDING : Standard Moldings
 FRAME WIDTH : 750 MM 29 9/16"
 FRAME HEIGHT : 914 MM 36"
 UNIT SHAPE : Ellipse
 LOWER HEIGHT : 678 MM 28 11/16"
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed

SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
 CERTIFIED : Impact Certified
 SASH TYPE : Triple Sash
 GLAZING STOP : Interior Profiled Glazing Stops
 GRILLE TYPE : SDL Grille
 GRILLE COLOR : White Clad (Std)
 GRILLE STYLE : Colonial Grille
 GRILLE PATTERN : 2W2H Pattern
 VERTICAL SIZE : 3/4" (19mm)
 HORIZONTAL SIZE : 3/4" (19mm)
 EXT PROFILE : Ogee Exterior Profile
 INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar

INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
 COATING : LOW E 366

GRILLE STD PATT : Grille is a Standard Pattern
 HARDWARE COLOR : No Hardware Color
 LOCK : No Locks
 SCREEN TYPE : No Screen
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

Line : 124.00 Model : 28AC 28 AWNING AND CASEMENT
PLine : 122.00 Qty : 1.00 U/M : EA

BUILD TYPE : Complete Unit
 UNIT STYLE : Casement Style
 UNIT TYPE : Traditional Operation
 OPERATION : Right Hand Operation
 ENHANCED DP : Enhanced Performance
 JAMB MOLDING : Standard Moldings
 FRAME WIDTH : 750 MM 29 9/16"
 FRAME HEIGHT : 1200 MM 47 1/4"
 UNIT SHAPE : Rectangular (Or Square)
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 INT GRILLE FIN : Primed
 JAMB : 116 MM 4 9/16"
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_3_366/B20-130/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 3 MM Glass Thickness
 LAMI GLASS : 10.1MM SGP 3.9/.090/3.9
 COATING : LOW E 366
 SPACER FINISH : BRZ Aluminum(20)Spacer Bar 13MM
 CERTIFIED : Impact Certified
 SASH TYPE : Triple Sash
 GLAZING STOP : Interior Profiled Glazing Stops

GRILLE TYPE : SDL Grille
 GRILLE COLOR : White Clad (Std)
 GRILLE STYLE : Colonial Grille
 GRILLE PATTERN : 2W2H Pattern
 VERTICAL SIZE : 3/4" (19mm)
 HORIZONTAL SIZE : 3/4" (19mm)
 EXT PROFILE : Ogee Exterior Profile
 INT PROFILE : Ogee Interior Profile
 GRILLE SPACER : 1 Airspace With Shadow Bars
 GRL SHADOW BAR : Deep Shadow Bar
 GRILLE STD PATT : Grille is a Standard Pattern
 HARDWARE COLOR : Oil Rubbed Bronze (Living Finish)
 LOCK : Concealed Locking Hdwr (Encore)
 HANDLE : C/W Crank Handle & Operator Cover
 ROTOGEAR : Encore Rotogear
 COVER TYPE : Provence Cover
 EGRESS : Egress not Required
 CORR RESISTANT : Stainless Steel Hdwr Required
 SCREEN TYPE : STD Aluminum Screen
 SCREEN COLOR : White (Std)
 MESH COLOR : Less Visible Screen (High Trans)
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

Line : 125.00	Model : 49CM	COMPOSITE UNIT MODEL			(D)
Location: _Bunkroom		Cubic Feet: 26.000			
Qty : 2.00	U/M : EA	List : 5615.01	Disc% : 23.25	Net : 4,309.52	Total : 8,619.04

CONFIGURATION : Unit / Unit
 SUB 1 : 28AC CAS ELP 0750X0914 F //
 SUB 2 : 28AC CAS RCT 0750X1200 F
 FRAME WIDTH : 750 MM 29 9/16"
 FRAME HEIGHT : 2115 MM 83 5/16"
 LOWER HEIGHT : 1878 MM 73 15/16"
 RADIUS : 612 MM 24 1/8"
 SPECIES : Douglas Fir
 JAMB : 116 MM 4 9/16"
 UNIT SHAPE : Ellipse
 FRAME FINISH : White Clad (Std)
 INT FRAME FIN : Primed
 BRICKMOLD : No Exterior Casings Required

CBSILLATTCH : No Casing Sub sill/Sillnose
 BRICKMOLD FIN : No Casing Color
 DRIPCAP : Snap On Drip cap
 FLANGE : All Four Sides
 DRAWING# : 31689-03-00A
 APPROVAL# : 31689-03-00A
 PACKAGING : Standard Packaging
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

Line : 126.00 Model : 28AC 28 AWNING AND CASEMENT
 PLine : 125.00 Qty : 2.00 U/M : EA

BUILD TYPE	: Complete Unit	SPACER FINISH	: BRZ Aluminum(20)Spacer Bar 13MM
UNIT STYLE	: Casement Style	CERTIFIED	: Impact Certified
UNIT TYPE	: Traditional Operation	SASH TYPE	: Triple Sash
OPERATION	: Fixed	GLAZING STOP	: Interior Profiled Glazing Stops
ENHANCED DP	: Enhanced Performance	GRILLE TYPE	: SDL Grille
JAMB MOLDING	: Standard Moldings	GRILLE COLOR	: White Clad (Std)
FRAME WIDTH	: 750 MM 29 9/16"	GRILLE STYLE	: Colonial Grille
FRAME HEIGHT	: 914 MM 36"	GRILLE PATTERN	: 2W2H Pattern
UNIT SHAPE	: Ellipse	VERTICAL SIZE	: 3/4" (19mm)
LOWER HEIGHT	: 678 MM 26 11/16"	HORIZONTAL SIZE	: 3/4" (19mm)
SPECIES	: Douglas Fir	EXT PROFILE	: Ogee Exterior Profile
FRAME FINISH	: White Clad (Std)	INT PROFILE	: Ogee Interior Profile
SASH FINISH	: Sash Color Matches Frame Color	GRILLE SPACER	: 1 Airspace With Shadow Bars
INT FRAME FIN	: Primed	GRL SHADOW BAR	: Deep Shadow Bar
INT SASH FIN	: Primed	GRILLE STD PATT	: Grille is a Standard Pattern
INT GRILLE FIN	: Primed	HARDWARE COLOR	: No Hardware Color
JAMB	: 116 MM 4 9/16"	LOCK	: No Locks
GLAZING	: Stormforce Series IP D-Missile	SCREEN TYPE	: No Screen
GLZ CONFIG	: CLR_3_366/B20-130/CLR_10.1SGP_NOC	QUALITY INSPECT	: QC must Inspect Prior to PKG
GLASS TINT	: Clear Glass	WATER TEST	: Water Tested in the Field
GLASS THICKNESS	: 3 MM Glass Thickness	FRMNOSE	: Standard
LAMI GLASS	: 10.1MM SGP 3.9/.090/3.9	MIDCMT	: AT:TO BE TOTAL JAMB & SASH BACK PRIMED**
COATING	: LOW E 366		

Line : 127.00 Model : 28AC 28 AWNING AND CASEMENT
 PLine : 125.00 Qty : 2.00 U/M : EA

BUILD TYPE	: Complete Unit	SPACER FINISH	: BRZ Aluminum(20)Spacer Bar 13MM
UNIT STYLE	: Casement Style	CERTIFIED	: Impact Certified
UNIT TYPE	: Traditional Operation	SASH TYPE	: Triple Sash
OPERATION	: Fixed	GLAZING STOP	: Interior Profiled Glazing Stops
ENHANCED DP	: Enhanced Performance	GRILLE TYPE	: SDL Grille
JAMB MOLDING	: Standard Moldings	GRILLE COLOR	: White Clad (Std)
FRAME WIDTH	: 760 MM 29 9/16"	GRILLE STYLE	: Colonial Grille
FRAME HEIGHT	: 1200 MM 47 1/4"	GRILLE PATTERN	: 2W2H Pattern
UNIT SHAPE	: Rectangular (Or Square)	VERTICAL SIZE	: 3/4" (19mm)
SPECIES	: Douglas Fir	HORIZONTAL SIZE	: 3/4" (19mm)
FRAME FINISH	: White Clad (Std)	EXT PROFILE	: Ogee Exterior Profile
SASH FINISH	: Sash Color Matches Frame Color	INT PROFILE	: Ogee Interior Profile
INT FRAME FIN	: Primed	GRILLE SPACER	: 1 Airspace With Shadow Bars
INT SASH FIN	: Primed	GRL SHADOW BAR	: Deep Shadow Bar
INT GRILLE FIN	: Primed	GRILLE STD PATT	: Grille is a Standard Pattern
JAMB	: 116 MM 4 9/16"	HARDWARE COLOR	: No Hardware Color
GLAZING	: Stormforce Series IP D-Missile	LOCK	: No Locks
GLZ CONFIG	: CLR_3_366/B20-130/CLR_10.1SGP_NOC	SCREEN TYPE	: No Screen
GLASS TINT	: Clear Glass	QUALITY INSPECT	: QC must Inspect Prior to PKG
GLASS THICKNESS	: 3 MM Glass Thickness	WATER TEST	: Water Tested in the Field
LAMI GLASS	: 10.1MM SGP 3.9/.090/3.9	FRMNOSE	: Standard
COATING	: LOW E 366	MIDCMT	: AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

*

Line : 128.00	Model : 18TDT	18 TERRACE DOOR TRANSOM			(D)
Location: Study			Cubic Feet: 18.000		
Qty : 2.00	U/M : EA	List :	2397.00	Disc% : 23.25	Net : 1,839.70 Total : 3,679.40

BUILD TYPE : Complete Unit
 UNIT STYLE : To Match French Door
 PANELS WIDE : 2
 FRAME WIDTH : 1829 MM 72"
 FRAME HEIGHT : 600 MM 23 5/8"
 UNIT SHAPE : Rectangular (Or Square)
 SPECIES : Douglas Fir
 FRAME FINISH : White Clad (Std)
 SASH FINISH : Sash Color Matches Frame Color
 INT FRAME FIN : Primed
 INT SASH FIN : Primed
 VGINT : Vert Grain Int - Stiles & Rails
 JAMB : 116 MM 4 9/16"
 BRICKMOLD : No Exterior Casings Required
 BRICKMOLD FIN : No Casing Color
 SUBSILL : No Casing Subsill/Sillnose
 GLAZING : Stormforce Series IP D-Missile
 GLZ CONFIG : CLR_4_366/B20-115/CLR_10.1SGP_NOC
 GLASS TINT : Clear Glass
 GLASS THICKNESS : 4 MM Glass Thickness

LAMI GLASS : 10.1MM SGP 3.9/090/3.9
 COATING : LOW E 366
 CERTIFIED : Impact Certified
 SPACER FINISH : BRZ Aluminum(20)Spacer Bar 11.5MM
 GLAZING STOP : Interior Profiled Glazing Stops
 FRAME&SASH TYPE : C/W TD Transom Frame and TD Sash
 TOP RAIL : 2 1/16" (53mm) Top Rail
 BOTTOM RAIL : 2 1/16" (53mm) Bottom Rail
 STILE TYLE : 4 5/16" (110mm) Standard Stile
 FLANGE : Head, Left, Right
 DRIPCAP : Snap On DripCap
 PKG : Standard Packaging
 DRAWING# : 20075-07-00A
 APPROVAL# : 26075-07-00A
 QUALITY INSPECT : QC must Inspect Prior to PKG
 WATER TEST : Water Tested in the Field
 FRMNOSE : Standard
 PANELTHK : 1 3/4" Panel Thickness
 MIDCMT : AT:TO BE TOTAL JAMB & SASH BACK PRIMED**

Total number of items :	47.00	SubTotal	110,739.61
Total Cubic Feet :	420.00	Federal Tax Number :	.00
Shipping Terms :	PRE-PAID	Prov/State Tax Number :	FL STATE TAX 6,644.38
Payment Terms :	C.O.D.		GRAND TOTAL - US 117,383.99

Please review and report any errors or changes immediately.
 Loewen, at its sole discretion, will seek to accommodate changes to orders that have been submitted.
 All changes requested after submission will be subject to additional charges as determined by Loewen.
 There will be instances where changes to an order in progress will not be possible.
 Load dates may be modified due to the changes requested.

All quotes and orders that meet any of the following criteria must be approved by Loewen prior to quotation or bid submittal by dealer;

- (i) valued at over \$300,000 Net Loewen sell price, or
- (ii) for Commercial building projects, or
- (iii) with specification for product performance and/or on-site testing

Loewen reserves the right to require special terms and conditions on sales of these projects or to decline them outright.

Loewen shall have no liability of any kind for any losses or damages due to any delays in fulfilling orders, delays in meeting delivery dates or delays in shipping, or any losses or damages resulting from causes beyond the immediate and direct control of Loewen.